

HONDA



Compact Tiller



www.hondapowerproducts.ph
Facebook.com/HondaPowerProductsPH

*Photo may vary from actual unit.

Specifications

| Model | | FJ 500 |
|-----------------------------|--------------------------------|--|
| Engine | Engine Name | GX160H1 |
| | Total Displacement | 163 cm ³ (9.9 cu in) |
| | Fuel Type | Gasoline with a pump octane rating of 86 or higher |
| | Net Power (SAE J1349) *1 | 3.6 kW @ 3, 600 rpm |
| | Maximum net torque (SAE J1349) | 10.3 N-m @ 2, 500 rpm |
| | Fuel tank capacity | 3.1 Liters (0.82 US gal, 0.68 Imp gal) |
| | Fuel consumption | 1.4 Liters (0.37 US gal, 0.31 Imp gal)/h |
| | Starter System | Recoil Starter |
| | Air Cleaner System | Dual Type |
| Clutch | Clutch Type | Belt Tension Type |
| | Operation Method | Manual Lever (2 Motion) |
| Transmission | No. of Gears | Forward 2 / Reverse 1 |
| | Speed Reduction Ratio | Forward ①45.3 ②31.9 / Reverse 128.6 |
| | Axle Rotating Speed (rpm) | Forward ①79.5 ②112.9 / Reverse 28.0 |
| | Rotor ASSY | φ300 |
| Rotor Area | Tine Diameter (mm) | 300 |
| | Tillage Width (mm) | 350 (2 rotor), 630 (4 rotor), 900 (6 rotor) |
| | Retractable Wheel | ○ |
| Dimensions (L x W x H) (mm) | | 1435 x 925 x 1015 |
| Dry Weight (kg) | | 62 |

Note: Specifications may change without prior notice.

FJ 500 Features

Handling

The retractable wheel allows for easy storage and transport to the job site.

Serviceability

The snorkel air cleaner and quick drain system allow for easy maintenance and product longevity.

Tilling Performance

Powered by a high output 4 stroke OHV engine compliant with Euro2 emission standards, 3 part detachable tines and an adjustable depth bar enable operation in a wide variety of conditions and applications.

Safety

With oversize fenders and dual motion clutch, the FJ 500 provides safety and peace of mind while also complying with EN709 safety regulations.

Operation

The tilling speed/direction control which improve maneuverability in tight places allow this mid-tine rotary tiller to operate in a variety of spaces and soil conditions.



Weeding



Tilling

*Photos may vary from actual unit.

Attachments:

| | | |
|---|---|---|
| Front Weight (4.1kg) | Deep Rotor | French rotor 4 Parts Detachable |
|  |  |  |

Honda Philippines, Inc.
Lot 34, Phase 1-B, Road 3, First Philippine Industrial Park,
Tanauan City, Batangas

Sales Hotline:
(02) 756-7300 or
(02) 581-6700 loc. 7078

Customer Service Hotline:
1-800-10-HONDAPH
(1-800-10-4663274)

Authorized Dealer: